FENNER V-pulley for taper bush section SPZ - 3 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210. DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL
Type: Z/SPZ/QXPZ
Number of grooves: 3
Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
18	22	
15	25	
15	25	0
8	32	
	32	8
2.5	45	2.5

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
67	1108		Cast iron	9.7				11421687
71	1108	6	Cast iron	9.7	18	22		11421690
75	1210	6	Cast iron	9.7	15	25		11421693
80	1210		Cast iron	9.7				11421697
85	1610	6	Cast iron	9.7	15	25		11421701
90	1610		Cast iron	9.7				11421706
95	1610	6	Cast iron	9.7	15	25		11421710
100	1610		Cast iron	9.7	15	25	0	11421716
112	2012	6	Cast iron	9.7	8	32		11421728
118	2012		Cast iron	9.7				11421734
125	2012	2	Cast iron	9.7		32	8	11421741
132	2012	2	Cast iron	9.7		32	8	11421748
140	2012		Cast iron	9.7				11421754
150	2012		Cast iron	9.7				11421760
160	2012		Cast iron	9.7				11421766
180	2012		Cast iron	9.7				11421777
190	2012		Cast iron	9.7				11422343
200	2012		Cast iron	9.7				11421784
224	2012		Cast iron	9.7				11421790
250	2012		Cast iron	9.7				11421796
355	2517	4	Cast iron	9.7	2.5	45	2.5	11421814
400	2517	4	Cast iron	9.7	2.5	45	2.5	11421819
450	2517		Cast iron	9.7				11459811

PR2277168452067891_EN_19.05.2024

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
500	2517		Cast iron	9.7				11421824

PR2277168452067891_EN_19.05.2024

ERIKS NV | Tel.: +32 14 33 62 30 | E-mail: powertransmissions@eriks.be