



FENNER V-pulley for taper bush section SPB - 2 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 2

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
	19	
1	45	
0.5	45	0.5
4	76	4
3.5	51	3.5
11	65	11

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
112	2012	2	Cast iron	16.1		19		11422026
125	2012		Cast iron	16.1				11422036
132	2012		Cast iron	16.1				11422041
140	2012		Cast iron	16.1				11422047
150	2012		Cast iron	16.1				11422053
160	2012		Cast iron	16.1				11422060
170	2012		Cast iron	16.1				11422067
180	2517		Cast iron	16.1				11422075
200	2517		Cast iron	16.1				11422091
212	2517		Cast iron	16.1				11422098
236	2517	8	Cast iron	16.1	1	45		11422113
250	2517		Cast iron	16.1				13924860
280	2517	8	Cast iron	16.1	1	45		11422128
300	2517	8	Cast iron	16.1	0.5	45	0.5	11422135
315	2517	8	Cast iron	16.1	1	45		11422141
335	2517	8	Cast iron	16.1	0.5	45	0.5	11422148
355	3020		Cast iron	16.1				11422155
450	3020		Cast iron	16.1				11422175
500	3020		Cast iron	16.1				11422182
560	3020	4	Cast iron	16.1	4	76	4	11422188
630	3020	4	Cast iron	16.1	3.5	51	3.5	11422196
800	3525	4	Cast iron	16.1	11	65	11	11422204

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.