



FENNER V-pulley for taper bush section SPZ - 6 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: Z/SPZ/QXPZ

Number of grooves: 6

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
44	32	0
44	32	44
31	45	31
	45	
16	45	16
13	51	13
6	65	6

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
100	2012	6	Cast iron	9.7	44	32	0	11421719
106	2012	6	Cast iron	9.7	44	32	0	11421725
112	2012	6	Cast iron	9.7	44	32	44	11421731
118	2517	6	Cast iron	9.7	31	45	31	11421737
125	2517	6	Cast iron	9.7	31	45	31	11421745
132	2517		Cast iron	9.7				11421751
140	2517		Cast iron	9.7				11421757
150	2517	2	Cast iron	9.7		45		11421763
160	2517	2	Cast iron	9.7		45		11421769
170	2517		Cast iron	9.7				11421774
190	2517	3	Cast iron	9.7	16	45	16	11422346
200	2517	3	Cast iron	9.7	16	45	16	11421787
224	2517	7	Cast iron	9.7	16	45	16	11421793
250	2517		Cast iron	9.7				11421799
280	2517	7	Cast iron	9.7	16	45	16	11421805
315	2517		Cast iron	9.7				11421811
450	3020	5	Cast iron	9.7	13	51	13	11459813
500	3020	5	Cast iron	9.7	13	51	13	11421826
630	3525	5	Cast iron	9.7	6	65	6	11459826

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.