

ECON® Fire fighting valve Type: 2057LM Aluminium Inclined Flange



Characteristics

Type: 2057LM

Construction type: Inclined

Housing material: Aluminium

Material quality: G-ALMgSi3

Connection: Flange

Connection 2: Storz coupling

Flange finish: Flat face

Operation: Hand wheel, non-rising with non-rising stem

Type of bonnet: Flanged

Spindle material: Aluminium

Primary spindle seal material: EPDM

Material bonnet: Aluminium

Bonnet gasket material: EPDM

Material storz coupling: Aluminium

Actuator material: Aluminium

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 80 °C

Maximum pressure difference at 20 °C: 10 bar

Application

- Recommended in: Utilities

DN	A	L2	H (open)	M	Lug distance	Weight
mm	mm	mm	mm	mm	mm	kg
40	150	145	190	120	51	7.1
50	165	160	190	120	66	8.2
65	185	190	220	140	81	11.4

Pressure class	Maximum medium temperature
PN10	80 °C

Norm	Nominal inner diameter	Lug distance	Pressure rating	Face to Face length	Sealing	Article
		mm		mm		
EN (DIN)	DN50	66	PN10	888888	EPDM	13395320
EN (DIN)	DN65	81	PN10	888888	EPDM	13395321

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.