



BURKERT Globe valve free-flow Type 31095 series 2000 stainless steel entry below the valve pneumatic internal thread

Characteristics

Function: Two-way valve
Construction type: Free-flow
Housing material: Stainless steel
Material quality: 1.4404
Process connection: Internal thread [BSPP]
Standard connection: DIN ISO 228-1
Face to Face norm: Manufacturer standard
Type of disc: Fixed disc
Actuation: Pressure below the valve
Type of actuator: Pneumatic piston
Function actuator: Spring closing
Position indicator: Yes
Stem seal type: Roof cuffs
Primary spindle seal material: PTFE
Material disk sealing: PTFE
Material disc: 1.4401
Spindle material: Stainless steel
Material bonnet: 1.4401
Bonnet gasket material: Graphite
Level of protection (IP value): IP67
Approvals: ATEX IECEx
Max. viscosity: 600 mm²/s
Medium temperature: -10 / 185 °C

Application

- Neutral and slightly aggressive liquids.
- Steam.

Technical Information

- Water hammer damping for applications of non-compressible media.
- High flow capacity.
- Spring closure.
- Sealing in 2 directions.
- Process pressure below the valve.
- Low control air consumption
- Easy fitting.
- Maintenance free.
- Long service life ± 3 million switching operations.

Options

- 3-way control valve for direct mounting, type 33060 and type 33061, or via a control valve cluster.
- Mechanical valve position indicator with or without built-in control valve.
- Manual emergency operation.
- Stroke limiter for opening and/or closing.
- Piston operation with NAMUR connection for control valves.
- Piston operation of PPS ø 53–101 mm: Ambient temperature 5–140°C.
- Piston operation of PPS ø 127–153mm: Ambient temperature 5–90°C.
- Briefly to 140°C and pilot pressure max. 7bar.
- Process connection in NPT.
- Short valve body with a built-in length similar to that of the old 0251/2002 series.
- Double-acting piston operation without return spring.

Size process connection	Pressure rating	Kv value m ³ /h	Closing pressure bar	Type coding actuator	Pilot pressure	Actuator material	Ex-class	ATEX Zone	Ambient temperature °C	Article
3/8" [10]	PN25	3.7	15	C40	4 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 30	12036227
1/2" [15]	PN25	3.8	15	C40	4 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 30	13417366
3/4" [20]	PN16	9	20	E63	4.5 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 55	11815027
3/4" [20]	PN25	8.5	11	D50	4.1 - 10 bar	PPS	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	5 / 130	13417367

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Size process connection	Pressure rating	Kv value m ³ /h	Closing pressure bar	Type coding actuator	Pilot pressure	Actuator material	Ex-class	ATEX Zone	Ambient temperature °C	Article
3/4" [20]	PN25	8.5	11	D50	4.1 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 40	12702808
1" [25]	PN25	18	11	E63	4.5 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 55	12183784
1" [25]	PN25	18	25	F80	5 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	13417365
1.1/4" [32]	PN25	27	14	F80	5 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	12183783
1.1/2" [40]	PN25	38	9	F80	5 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	13391288
2" [50]	PN25	55	7	G100	4.4 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	11815020
2" [50]	PN25	55	20	H125	5.7 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	12036226
2.1/2" [65]	PN25	90	12	H125	5.7 - 10 bar	PA	II 2G Ex h IIC T4 Gb / II 2D Ex h IIIC T135 °C Db	Zone 1 / 21	-10 / 60	12036229

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.