

Support stand for bicycle rack, model 4000

Bicycle stand parker, model 4000, single-sided

Stand parker with optimised stability

The extremely high bracket shape ensures wheel alignment to protect the rims and tyres.

Sturdy steel construction

with hot dip galvanising according to DIN EN ISO 1461 for corrosion protected steel construction. Base frame made of 35-gauge angle steel.

Suitable for standard wheel types

Wheel alignment made of 18 gauge circular tube. Setting angle: 90°. Setting bracket for tyre widths up to 55 mm -

also suitable for mountain bikes.

Suitable for installation in rows

front side prepared for floor mounting. Also allows fitting to series system.

Description	Article
Bicycle rack, upright rack, one-sided L105mm 3 bicycle parking points, galvanised	14340364
Bicycle rack, upright rack, one-sided L140mm 4 bicycle parking points, galvanised	12970059
Bicycle rack, upright rack, one-sided L175mm 5 bicycle parking points, galvanised	12970080
Bicycle rack, upright rack, one-sided L210mm 6 bicycle parking points, galvanised	12970104
Bicycle rack, upright rack, one-sided L70mm 2 bicycle parking points, galvanised	14340363
Bicycle rack, upright rack, two-sided L105mm 6 bicycle parking points, galvanised	14340366
Bicycle rack, upright rack, two-sided L1400mm 8 bicycle parking points, galvanised, welded	14340367
Bicycle rack, upright rack, two-sided L175mm 10 bicycle parking points, galvanised	14340368
Bicycle rack, upright rack, two-sided L210mm 12 bicycle parking points, galvanised	14340369
Bicycle rack, upright rack, two-sided L70mm 4 bicycle parking points, galvanised	14340365

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

PR2803770666084994_EN_10.05.2024