



WALVOIL Monobloc valve QM45

Characteristics

Number of sections: 8

Operation: Manual

Pressure feed-through: No

Model	Max. operating pressure bar	Max. oilflow l/min	Max. pressure on T bar	Connections	Article
Conventional	300	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525674
Conventional	300	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525676
Conventional	300	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525677
Conventional	300	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525678
Conventional	300	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525679
Conventional	320	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525673
Conventional	350	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525671
Conventional	350	60	25	A,B,P,T,P2,T2: 1/2"BSP	12525672

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.