



AKO Pinch valve Series: VMC-G Type: 210DR Pneumatic operated Internal thread (BSPP)

Characteristics

Series: VMC-G

Type: 210DR

Norm: EN (DIN)

Housing material: Stainless steel

Material quality: AISi10Mg

Connection: Internal thread (BSPP)

Standard thread connection: ISO 228-1


Operation: Pneumatic operated

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 80 °C

Application

- Recommended in: Food & Beverages



Nominal inner diameter	Material code hose/sleeve	Hose/sleeve material	Maximum control pressure bar	Maximum pressure difference at 20 °C bar	Article
1" [25]	NR-X	NR (natural rubber)	8	6	12327269
1.1/4" [32]	NR-X	NR (natural rubber)	8	6	12362038
1.1/2" [40]	NR-X	NR (natural rubber)	8	6	12226153
2" [50]	NR-X	NR (natural rubber)	8	6	12311743
3/8" [10]	NR-X	NR (natural rubber)	8	6	12356112
1/2" [15]	NR-L	NR (natural rubber)	8	6	12369371
3/4" [20]	EPDM	EPDM	8	6	12362037
1.1/4" [32]	EPDM	EPDM	8	6	12304520

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.