



WALVOIL 2SP-A group 2, flange: B80C (100x72 mm), cylindrical shaft 12: 15 mm, N connections: flange

Characteristics

Mounting flange: German (100x72 mm) ø 80 mm

Drive shaft: Cylindrical 15 mm

Execution (single/tandem): Single

Type: External Gear Pump

Position oil ports: Side

Seal material: NBR

Shaft seal type: Standard

Displacement cm ³ /r	Direction of rotation	Max. operating pressure bar	Inlet port	Outlet port	Code	Article
4	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-040-D-B80C-B- N-12-0-N	13339471
4	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-040-S-B80C-B- N-12-0-N	13339491
6	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-060-D-B80C-B- N-12-0-N	13339472
6	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-060-S-B80C-B- N-12-0-N	13339492
11	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-110-D-B80C-B- N-12-0-N	13339484
11	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-110-S-B80C-B- N-12-0-N	13339494
14	Clockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-140-D-B80C-B- N-12-0-N	13339485
14	Counterclockwise	250	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-140-S-B80C-B- N-12-0-N	13339495
26	Clockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-260-D-B80C-B- N-12-0-N	13339489
26	Counterclockwise	170	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-260-S-B80C-B- N-12-0-N	13339499
8,5	Clockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-080-D-B80C-B- N-12-0-N	13339483
8,5	Counterclockwise	250	European flanged ports 30/13/M6	European flanged ports 30/13/M6	2SP-A-080-S-B80C-B- N-12-0-N	13339493
16,5	Clockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-160-D-B80C-B- N-12-0-N	13339486
16,5	Counterclockwise	230	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-160-S-B80C-B- N-12-0-N	13339496
19,5	Clockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-190-D-B80C-B- N-12-0-N	13339487
19,5	Counterclockwise	210	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-190-S-B80C-B- N-12-0-N	13339497
22,5	Clockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-220-D-B80C-B- N-12-0-N	13339488
22,5	Counterclockwise	190	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-220-S-B80C-B- N-12-0-N	13339498
31,5	Clockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-310-D-B80C-B- N-12-0-N	13339490
31,5	Counterclockwise	130	European flanged ports 40/19/M8	European flanged ports 30/13/M6	2SP-A-310-S-B80C-B- N-12-0-N	13339500

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.