



BURKERT Solenoid valve 2/2 Type: 32256 series 6212 stainless steel internal thread

Characteristics

Series: 6212
Type: 32256
Function: Normally closed (NC)
Actuation: Indirect-acting
Electrical connection: Plug EN 175301-803 type C
Housing material: Stainless steel
Material quality: 1.4310
Material coil housing: Epoxy
Membrane material: FPM (FKM)
Working time: 40 % max. 20 min.

Characteristics [2]

Level of protection (IP value): IP65
Emergency manual operation: None
Explosion-proof: No
Medium temperature: From 0 °C to 50 °C
Ambient temperature: From 0 °C to 55 °C

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Sealing	Article
		mm	m³/h	bar	bar					
1/2" [15]	Internal thread (BSPP)	10	1.9	0.5	10	SPC16 35334	24V DC	3.4 W	FPM (FKM)	13340027
1/2" [15]	Internal thread (BSPP)	10	1.9	0.5	10	SPC16 35335	230V - 240V AC/DC	4 W	FPM (FKM)	13340026
1/2" [15]	Internal thread (BSPP)	13	3.6	0.5	10	SPC16 35334	24V DC	3.4 W	FPM (FKM)	13340029
1/2" [15]	Internal thread (BSPP)	13	3.6	0.5	10	SPC16 35335	230V - 240V AC/DC	4 W	FPM (FKM)	13340028
1" [25]	Internal thread (BSPP)	20	8.3	0.5	10	SPC16 35334	24V DC	3.4 W	FPM (FKM)	13339994
1" [25]	Internal thread (BSPP)	20	8.3	0.5	10	SPC16 35335	230V - 240V AC/DC	4 W	FPM (FKM)	13339995
3/4" [20]	Internal thread (BSPP)	13	3.6	0.5	10	SPC16 35334	24V DC	3.4 W	FPM (FKM)	13340031

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.