



BURKERT Solenoid valve 2/2 Type: 32248 series 6211 brass internal thread

Characteristics

Series: 6211
Type: 32248
Function: Normally closed (NC)
Actuation: Indirect-acting
Electrical connection: Plug EN 175301-803 type B
Housing material: Brass
Material quality: CW617N [CuZn40Pb2]
Sealing: NBR
Material coil housing: Epoxy
Material shorting ring: Copper
Membrane material: NBR

Characteristics [2]

Working time: 100 %
Level of protection (IP value): IP65
Emergency manual operation: None
Explosion-proof: No
Medium temperature: From 0 °C to 70 °C
Ambient temperature: From 0 °C to 55 °C

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m³/h	bar	bar					
1/2" [15]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	24V AC	4 W / 6 VA	9 VA	13340112
1/2" [15]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340110
1/2" [15]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340111
1/2" [15]	Internal thread (BSPP)	13	3.6	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340100
1/2" [15]	Internal thread (BSPP)	13	3.6	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340122
1" [25]	Internal thread (BSPP)	20	8.3	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340118
1" [25]	Internal thread (BSPP)	20	8.3	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340102
3/4" [20]	Internal thread (BSPP)	13	3.6	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340113
3/4" [20]	Internal thread (BSPP)	13	3.6	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340114
3/4" [20]	Internal thread (BSPP)	20	8.3	0.5	10	SPC22 35151	24V AC	4 W / 6 VA	9 VA	13340116
3/4" [20]	Internal thread (BSPP)	20	8.3	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340115
3/4" [20]	Internal thread (BSPP)	20	8.3	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340117
3/8" [10]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	24V AC	4 W / 6 VA	9 VA	13340120
3/8" [10]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	24V DC	4 W (hot) / 5 W (cold)		13340119
3/8" [10]	Internal thread (BSPP)	10	1.9	0.5	10	SPC22 35151	230V AC	4 W / 6 VA	9 VA	13340121

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.