



LEADER PTFE flange gasket CLIPPERLON 2135 EN 1514-1



Characteristics

Series: CLIPPERLON

Type: 2135

Norm: EN 1514-1 IBC

Material structure: PTFE expanded

Marking: Embossed

Temperature range: -240 / 230 °C

Max. pressure: 40 bar

Suitable for medium: Weak Acids, Alkalis, Cryogenic, Chlorine Water < 5% (7782-50-5), Weak Alkalis, Pharma, Air (compressed air), Strong Alkalis, Acids, Food & Beverages, Chlorine, gaseous (7782-50-5), Solvents, Refrigerants, Strong acids (except hydrofluoric)

Approval according to: USP Class VI 121 C, TA-Luft, EC1935 (10/2011), Blow out VDI2200

Application

- Recommended in: Chemical, Food & Beverages, Pharma

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN10	PN10/40	46	18	1.5	13366575
DN10	PN10/40	46	18	2	13366666
DN10	PN10/40	46	18	3	13366550
DN15	PN10/40	51	22	1.5	13366576
DN15	PN10/40	51	22	2	13366618
DN15	PN10/40	51	22	3	13366551
DN20	PN10/40	61	27	1.5	13366577
DN20	PN10/40	61	27	2	13366620
DN20	PN10/40	61	27	3	13366542
DN25	PN10/40	71	34	1.5	13366578
DN25	PN10/40	71	34	2	13366621
DN25	PN10/40	71	34	3	13366543
DN32	PN10/40	82	43	1.5	13366579
DN32	PN10/40	82	43	2	13366622
DN32	PN10/40	82	43	3	13366544
DN40	PN10/40	92	49	1.5	13366580
DN40	PN10/40	92	49	2	13366623
DN40	PN10/40	92	49	3	13366545
DN50	PN10/40	107	61	1.5	13366581
DN50	PN10/40	107	61	2	13366609
DN50	PN10/40	107	61	3	13366540
DN65	PN10/40	127	77	1.5	13366582
DN65	PN10/40	127	77	2	13366624
DN65	PN10/40	127	77	3	13366546
DN80	PN10/40	142	89	1.5	13366583
DN80	PN10/40	142	89	2	13366625
DN80	PN10/40	142	89	3	13366547
DN100	PN10/16	162	115	1.5	13366584
DN100	PN25/40	168	115	1.5	13366585
DN100	PN25/40	168	115	2	13366642
DN100	PN10/16	162	115	2	13366626
DN100	PN10/16	162	115	3	13366541
DN100	PN25/40	168	115	3	13366552

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN125	PN10/16	192	141	1.5	13366586
DN125	PN25/40	194	141	1.5	13366587
DN125	PN25/40	194	141	2	13366643
DN125	PN10/16	192	141	2	13366627
DN125	PN25/40	194	141	3	13366554
DN125	PN10/16	192	141	3	13366553
DN150	PN25/40	224	169	1.5	13366589
DN150	PN10/16	218	169	1.5	13366588
DN150	PN10/16	218	169	2	13366628
DN150	PN25/40	224	169	2	13366644
DN150	PN10/16	218	169	3	13366548
DN150	PN25/40	224	169	3	13366555
DN200	PN25	284	220	1.5	13366591
DN200	PN40	290	220	1.5	13366592
DN200	PN10/16	273	220	1.5	13366590
DN200	PN40	290	220	2	13366652
DN200	PN10/16	273	220	2	13366629
DN200	PN25	284	220	2	13366645
DN200	PN40	290	220	3	13366558
DN200	PN10/16	273	220	3	13366556
DN200	PN25	284	220	3	13366557
DN250	PN25	340	273	1.5	13366595
DN250	PN40	352	273	1.5	13366596
DN250	PN16	329	273	1.5	13366594
DN250	PN10	328	273	1.5	13366593
DN250	PN16	329	273	2	13366636
DN250	PN40	352	273	2	13366653
DN250	PN10	328	273	2	13366630
DN250	PN25	340	273	2	13366646
DN250	PN10	328	273	3	13366559
DN250	PN25	340	273	3	13366561
DN250	PN40	352	273	3	13366562
DN250	PN16	329	273	3	13366560
DN300	PN16	384	324	1.5	13366598
DN300	PN25	400	324	1.5	13366599
DN300	PN40	417	324	1.5	13366600
DN300	PN10	378	324	1.5	13366597
DN300	PN25	400	324	2	13366647
DN300	PN40	417	324	2	13366654
DN300	PN16	384	324	2	13366637
DN300	PN10	378	324	2	13366631
DN300	PN16	384	324	3	13366564
DN300	PN40	417	324	3	13366566
DN300	PN25	400	324	3	13366565
DN300	PN10	378	324	3	13366563
DN350	PN25	457	356	1.5	13366603
DN350	PN10	438	356	1.5	13366601
DN350	PN16	444	356	1.5	13366602
DN350	PN40	474	356	1.5	13366604
DN350	PN25	457	356	2	13366648
DN350	PN10	438	356	2	13366632
DN350	PN40	474	356	2	13366655
DN350	PN16	444	356	2	13366638

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal diameter	Flange pressure stage	Outer diameter mm	Inner diameter mm	Thickness mm	Article
DN350	PN10	438	356	3	13366567
DN350	PN25	457	356	3	13366569
DN350	PN40	474	356	3	13366570
DN350	PN16	444	356	3	13366568
DN400	PN10	489	407	1.5	13366605
DN400	PN16	495	407	1.5	13366606
DN400	PN25	514	407	1.5	13366607
DN400	PN40	546	407	1.5	13366608
DN400	PN25	514	407	2	13366649
DN400	PN10	489	407	2	13366633
DN400	PN40	546	407	2	13366656
DN400	PN16	495	407	2	13366639
DN400	PN16	495	407	3	13366572
DN400	PN40	546	407	3	13366574
DN400	PN25	514	407	3	13366573
DN400	PN10	489	407	3	13366571
DN450	PN10	539	458	1.5	13366668
DN450	PN16	555	458	1.5	13366671
DN450	PN40	571	458	1.5	13366677
DN450	PN25	564	458	1.5	13366674
DN450	PN16	555	458	2	13366670
DN450	PN10	539	458	2	13366667
DN450	PN40	571	458	2	13366676
DN450	PN25	564	458	2	13366673
DN450	PN16	555	458	3	13366672
DN450	PN10	539	458	3	13366669
DN450	PN25	564	458	3	13366675
DN450	PN40	571	458	3	13366678
DN500	PN25	624	508	1.5	13366614
DN500	PN16	617	508	1.5	13366612
DN500	PN40	628	508	1.5	13366616
DN500	PN10	594	508	1.5	13366610
DN500	PN16	617	508	2	13366640
DN500	PN10	594	508	2	13366634
DN500	PN25	624	508	2	13366650
DN500	PN40	628	508	2	13366657
DN500	PN16	617	508	3	13366660
DN500	PN40	628	508	3	13366664
DN500	PN25	624	508	3	13366662
DN500	PN10	594	508	3	13366549
DN600	PN40	747	610	1.5	13366617
DN600	PN10	695	610	1.5	13366611
DN600	PN25	731	610	1.5	13366615
DN600	PN16	734	610	1.5	13366613
DN600	PN40	747	610	2	13366658
DN600	PN16	734	610	2	13366641
DN600	PN25	731	610	2	13366651
DN600	PN10	695	610	2	13366635
DN600	PN16	734	610	3	13366661
DN600	PN10	695	610	3	13366659
DN600	PN25	731	610	3	13366663
DN600	PN40	747	610	3	13366665

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.