


ECON® Positioner Type: 3303 NCS Quarter turn Single acting



Characteristics

Type: 3303 NCS
Transmission: Quarter turn
Execution: Positioner
Function actuator: Single acting
Input signal: 4 - 20 mA
Level of protection (IP value): IP66
Electrical connection: 1/2" NPT gland nut
Display: Yes
Stroke: 0 to 90°
With console: Yes
Standard actuator connection: VDI/VDE 385
With assembly set: Yes
Material housing: Aluminium
Material konsole: Steel



Application

- Valve position control to quarter turn (90 degrees), single-acting actuators.

Technical Information

- Including mounting bracket in accordance with VDI/VDE 3845.
- Ambient temperature at ATEX max. 60°C for T5 and 40°C for T6.

Options

- Pressure gauge block with 3 pressure gauges.
- Feedback 4–20 mA.
- Feedback 4–20 mA and HART communication.

Feed pressure	Connection voltage	Explosion-proof	Ex-class	ATEX Zone	Feedback signal	Ambient temperature °C	Article
1.4 to 7 bar	24V DC, 2-wire	No				-30 / 85	14463577
1.4 to 7 bar	24V DC, 2-wire	Yes	Ex ia IIC T5/T6 Gb, Ex ia IIIC T100°C/ T85°C Db IP6X	Zone 1 / 21	4 - 20 mA	-30 / 60	14463584

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.