

FENNER TriFlex tension force coupling TL

Fenner TriFlex cord-reinforced flexible couplings can be trusted for installation in the most diverse drive train applications, where resistance to shock stress is required and silent operation is important, such as fan, pump and compressor drives and machinery used in the agriculture, construction and marine industries.

Utilising the tension force principle, Fenner TriFlex couplings offer an efficient and cost effective alternative to traditional compression couplings. They are very compact, lightweight and low maintenance.

Characteristics

Series: TriFlex

Application

• Fenner® TriFlex Couplings are lightweight and compact –typically one third of the weight of a traditional compression couplingIndividual elements of the coupling can be replaced quickly without the need to move the motor or driven loadDrive train torque peaks can be effectively dampenedPrecise oscillatory tuning of the whole drive train can be achieved with easeFor special projects the stiffness of the reinforced cords in Fenner® TriFlex couplings can be individually adjusted in all directions to compensate for radial, axial and angular misalignmentIdeal for fans, pumps, compressors and mixers and agricultural machinery as a flexible connecting element

Construction

 Corrosion resistantTenpu® fibre technologyHigh quality elastomer element bodyHigh grade forged steel flanges10.9 grade bolts

Execution

All metal parts have electro plated corrosion resistant coating

Approval

ATEX certified

Туре	Size	Version	Material	Article
Coupling	75	F	Steel	13471448
Coupling	96	F	Steel	13471452
Coupling	120	F	Steel	13471476
Coupling	180	F	Steel	13471483
Coupling	220	F	Steel	13471487

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS

283809267166088997_EN_18.05.2024