



GRUNDFOS Submersible pump Series: SL - Vuilwater pomp

Characteristics

Series: SL

Connection: Flange

Pressure rating flange: PN10

Material pump casing: Cast iron

Material quality: EN-JL1030

Insulation class acc. to IEC: F

Maximum flow rate	Nominal volume flow rate	Max. immersion depth	Supply voltage	Length connecting cord	Rotational speed	Nominal current	Connection size	Pump height	Article
l/min	m³/h	m		m	rpm	A		mm	
57960	58	10	3 x 400-415V AC	10	2920	2.8	DN65	599	23499061
58320	58	10	1 x 230V AC	10	2920	6.1	DN65	599	23499058
58320	58	10	1 x 230V AC	10	2920	6.1	DN65	599	23499056
58320	58	10	3 x 400-415V AC	10	2920	2.8	DN65	599	23499059
58320	58	10	3 x 400-415V AC	10	2920	2.8	DN65	599	23499057
58320	58	10	3 x 400-415V AC	10	2920	2.8	DN65	599	23499063
64080	64	10	3 x 400-415V AC	10	2830	3.1	DN65	599	23499019
64080	64	10	3 x 400-415V AC	10	2830	3.1	DN65	599	23499017
64080	64	10	3 x 400-415V AC	10	2830	3.1	DN65	599	23499021
64440	64	10	1 x 230V AC	10	2830	7.4	DN65	599	23499014
64440	64	10	1 x 230V AC	10	2830	7.4	DN65	599	23499016
64440	64	10	1 x 230V AC	10	2830	7.4	DN65	599	23499015
70200	70	10	3 x 400-415V AC	10	2720	3.8	DN65	599	23499008
70200	70	10	3 x 400-415V AC	10	2720	3.8	DN65	599	23499010
70200	70	10	3 x 400-415V AC	10	2720	3.8	DN65	599	23499012

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.