


WALVOIL Adjustable descent control valves VRD



Characteristics

Version: Descent control valve

Type of valve: Adjustable



Max. operating pressure bar	Max. oilflow l/min	Adjustment range	Connections	Article
300	10	1,0 - 1,6 L/min	1/4" BSP	12560979
300	10	1,6 - 2,5 L/min	1/4" BSP	12560980
300	10	2,5 - 4,0 L/min	1/4" BSP	12560981
300	10	4,0 - 6,3 L/min	1/4" BSP	12560982
300	10	6,3 - 10 L/min	1/4" BSP	12560983
300	25	2,5 - 4,0 L/min	3/8" BSP	12497214
300	25	4,0 - 6,3 L/min	3/8" BSP	12560967
300	25	6,3 - 10 L/min	3/8" BSP	12560968
300	25	10 - 16 L/min	3/8" BSP	12560969
300	25	16 - 25 L/min	3/8" BSP	12560970
300	67	16 - 21 L/min	1/2" BSP	12497215
300	67	21 - 28 L/min	1/2" BSP	12560971
300	67	28 - 37 L/min	1/2" BSP	12560972
300	67	37 - 50 L/min	1/2" BSP	12560973
300	67	50 - 67 L/min	1/2" BSP	12560974
300	150	37 - 50 L/min	3/4" BSP	12560975
300	150	37-50 L/min	3/4" BSP	12497216
300	150	67 - 90 L/min	3/4" BSP	12560976
300	150	90 - 120 L/min	3/4" BSP	12560977
300	150	120 - 150 L/min	3/4" BSP	12560978

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.