



OLEODINAMICA MARCHESINI 2 ways flow divider V-EQ

These valves are used when two equal actuators, that are not mechanically couples, supplied by the same pump and controlled by a single valve, must move simultaneously both in extension and retraction.

Material:

- Body: zinc-plated steel.
- Internal parts: hardened and ground steel.
- Seals: BUNA N.

Mounting:

- Pipemounting: BSP ports.

Characteristics

Type: Inline mounting

Max. operating pressure: 250 bar



Volume flow l/min	Connections	Material	Article
1-3	C,A,B: 3/8" BSP	Cast iron	12495718
3-6	C,A,B: 3/8" BSP	Cast iron	12495719
6-10	C,A,B: 3/8" BSP	Cast iron	12495720
10-20	C,A,B: 3/8" BSP	Cast iron	12495721
20-32	C,A,B: 3/8" BSP	Cast iron	12495722
25-40	C: 1/2"BSP, A,B: 3/8" BSP	Cast iron	12495723
40-60	C: 1/2"BSP, A,B: 3/8" BSP	Cast iron	12495724
60-80	C: 1/2"BSP, A,B: 3/8" BSP	Cast iron	12495725

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.