



EUROTHERM Display/control panel fig. 36140

Digital PID processcontroller with relais output, alarm function, communication interface, and fully configurable and controllable via control panel.

Characteristics

Model: Process controller PID

Application

- In single control loop for temperature, pressure, flow or level control.

Technical Information

- Precision PID controller with auto-tuning.
- Sampling time: 250 ms [4 Hz].
- Precision: $\pm 0.25\%$ at 25°C and nominal power supply.
- Ramp soak timer and soft start function.
- Overshoot elimination.
- Recovery point (undo) function.
- High visibility three colour LED display.
- Simplified and customisable human interface.
- Wipedown front facia.
- Panel mounting.

Read-out:

- Measured value, preset value, status.
- Resolution display: -1999 to 9999.
- 2 Local setpoints.

Input:

- Thermocouples [K, J, N, R, S, B, L, T, C].
- Pt100 3-Wire version.
- 0 - 20 mA and 4 - 20 mA [via supplied shunt resistor].
- 0 - 80 mV [0 - 10V via external adapter, not supplied].

Control outputs:

- 1 x Relay.

Outputs:

- Relay: min. 100 mA at 12V DC / 2A max. at 264V AC, Ohmic circuit [3 x SPST / 1 x SPDT].
- Triac: 0.75 A [rms] 30 to 264V [rms], Ohmic circuit [special version of controller].

Logic input:

- Open $> 600\ \Omega$ / Closed $< 300\ \Omega$ $< 13\ \text{mA}$.

Options

Optiona Interfacing

- RS-485/ EIA485 [2-wire].
- Protocol MODBUS RTU.
- 1200 - 19200 Baud.

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Description	Article
Dig contr P108 36140 2R 24VAC/DC - PID on/off TK/Pt100/mV/mA 48x96 Input 1	13462597
Dig contr P108 36140 2R 24VAC/DC - PID on/off TK/Pt100/mV/mA 48x96 Input 2	13462599
Dig Contr P108 36140 2R 230VAC - PID on/off TK/Pt100/mV/mA 48x96 Input 1	13462596
Dig Contr P108 36140 2R 230VAC - PID on/off TK/Pt100/mV/mA 48x96 I1 RS485	13462595
Dig contr P108 36140 2R 24VAC/DC - PID on/off TK/Pt100/mV/mA 48x96 I2 RS485	13462598
Dig Contr P108 36140 2R 230VAC - PID on/off TK/Pt100/mV/mA 48x96 Input 0	13462594
Dig Contr P108 36140 4-20mA 24VAC/DC - PID TK/Pt100/mV/mA 48x96 Input 1	13462605
Dig Contr P108 36140 4-20mA 230VAC - PID TK/Pt100/mV/mA 48x96 I1 RS485	13462606
Dig Contr P108 36140 4-20mA 230VAC - PID TK/Pt100/mV/mA 48x96 Input 2	13226299
Dig Contr P108 36140 4-20mA 24VAC/DC - PID TK/Pt100/mV/mA 48x96 Input 0	13462603
Dig Contr P108 36140 4-20mA 24VAC/DC - PID TK/Pt100/mV/mA 48x96 I1 RS485	13462604

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.