

EUROTHERM Digital display fig. 36100 series 32H8i

Digital display series 32h8i with alarm function, transmitter supply, communication interface and analogue re-transmission. Provided with a 6-segment linearisation for level monitoring in non-linear vessels.




Characteristics

Series: 32H8i

Type: 36305

Model: Digital display



Technical Information

Read-out:

- LCD display with background lighting.
- 5-Digits, green and red.
- Measured value and unit.
- Resolution display: -99999 to 99999.
- 6-segment linearisation [e.g. for level measurement of non-linear tank].
- Memory of minimal and maximum value.
- Possibility of alarm text messages.

Measuring input:

- Thermocouples.
- Pt100 3-Wire version.
- 0 - 20 mA and 4 - 20 mA.
- 0 - 60 mV, 12 - 60 mV.
- 0 - 5V, 1 - 5V, 0 - 10V, 2 - 10V [via optional input adapter].
- Input refresh time: 110 ms.

Logic inputs:

- 2 Inputs, 12V DC, 40 mA max.

Outputs:

- Relay (SPDT), 264V AC, 2 A, Ohmic circuit.

Transmitter power supply:

- 24V DC / 20 mA.

Options

Interfacing:

- Isolated EIA232 or EIA485 2-wires.
- Protocol MODBUS RTU.

Outputs:

- Analogue retransmission signal: 0/4 - 20 mA, 0/1 - 5V, 0/2 - 10V.

Width mm	Height mm	Article
96	48	13462590
96	48	13462609
96	48	13462589
		13295357

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.