



FESTO Activated carbon filter LFX

Characteristics

Series: LFX

Ambient temperature: -10 / 60 °C

Material housing: Zinc die-casting

Manufacturer ID	Connection	Bowl guard	Maximum flow rate l/min	Ambient temperature °C	Bowl Material	Article
LFX-D-MINI		Metal	360	-10 / 60	Plastic	11646599
LFX-D-MIDI		Metal	900	-10 / 60	Plastic	11646600
LFX-D-MAXI		Metal	1100	-10 / 60	Plastic	11646601
LFX-1/2-D-MAXI	G1/2	Metal	1100	-10 / 60	Plastic	11646608
LFX-1/2-D-MIDI	G1/2	Metal	900	-10 / 60	Plastic	11646606
LFX-1/4-D-MIDI	G1/4	Metal	900	-10 / 60	Plastic	11646604
LFX-1/4-D-MINI	G1/4	Metal	360	-10 / 60	Plastic	11646615
LFX-1/8-D-MINI	G1/8	Metal	360	-10 / 60	Plastic	11646602
LFX-1-D-MAXI	G1	Metal	1100	-10 / 60	Plastic	11646610
LFX-3/4-D-MAXI	G3/4	Metal	1100	-10 / 60	Plastic	11646609
LFX-3/4-D-MIDI	G3/4	Metal	900	-10 / 60	Plastic	11646607
LFX-3/8-D-MINI	G3/8	Metal	360	-10 / 60	Plastic	11646603
LFX-3/8-D-MIDI	G3/8	Metal	900	-10 / 60	Plastic	11646605

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.