



FESTO Ball valve Series: VZBC Stainless steel Flange PN16/40

Characteristics

Series: VZBC

Construction type: 2-way

Housing construction: 1-part

Housing material: Stainless steel

Material quality: 1.4408

Connection: Flange

Top flange standard: ISO 5211

Nominal inner diameter	Pressure rating	Manual operation	Mounting flange	Mounting flange 2	Material ball	Seat material	Spindle material	Minimum medium temperature (continuous) °C	Maximum medium temperature (continuous) °C	Article
DN15	PN40	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	-10	200	14168379
DN20	PN40	Bare stem	F03	F04	Stainless steel	PTFE	Stainless steel	-10	200	14168389
DN25	PN40	Bare stem	F04	F05	Stainless steel	PTFE	Stainless steel	-10	200	13475632
DN32	PN40	Bare stem	F04	F05	Stainless steel	PTFE	Stainless steel	-10	200	14168401
DN40	PN40	Bare stem	F05	F07	Stainless steel	PTFE	Stainless steel	-10	200	14168409
DN50	PN40	Bare stem	F05	F07	Stainless steel	PTFE	Stainless steel	-10	200	14168419
DN65	PN16	Bare stem	F07		Stainless steel	PTFE	Stainless steel	-10	200	14168428
DN80	PN16	Bare stem	F07		Stainless steel	PTFE	Stainless steel	-10	200	14168431
DN100	PN16	Bare stem	F07	F10	Stainless steel	PTFE	Stainless steel	-10	200	14168444

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.