



FESTO One-Way flow control valve GRLA

Characteristics

Series: GRLA

Execution: One-way flow control valve

Mounting: Threaded

Seal material: TPE-U[PU]

Operating pressure: 0.3 / 10 bar

Temperature range: -10 / 60 °C

Fluid: Compressed air in accordance with
ISO8573-1:2010 [7:4:4]

Pneumatic connection 1	Article
	13395665
	14170095
	11627735
	11635220
	11630063
	11630046
	11630053
	23212068
	11630056
G1/2	1066981
G1/4	1066982
G1/4	1066710
G1/8	1066973
G1/8	23209851
G3/4	11630026
G3/8	1066980
M3	11634252
M5	11630023
M5	1066749
PK-3	23209729
PK-4	23209732
PK-4	23209730
PK-4	23209852
PK-6	23209853
PK-6	23209733
QS-3	11638269
QS-3	11638272
QS-3	11640062
QS-3	11640061
QS-3	11634267
QS-3	11634255
QS-4	23211172
QS-4	23209857
QS-4	23211631
QS-4	11638270
QS-4	23211354
QS-6	11316479
QS-6	11648006
QS-6	23211418
QS-6	23211604

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Pneumatic connection 1	Article
QS-6	23211427
QS-6	23210836
QS-6	11647142
QS-6	11647139
QS-6	23211422
QS-6	11316477
QS-6	23209859
QS-6	11632464
QS-8	11647138
QS-8	23211444
QS-8	23210775
QS-8	23209858
QS-8	11545467
QS-8	11647140
QS-8	11648007
QS-8	23213159
QS-8	23211321
QS-10	23211461
QS-10	11647141
QS-10	11647143
QS-12	11647144
QS-12	23211885

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.