

FESTO Pressure regulator combination LRB-K

Characteristics

Series: LRB-K

Flow rate: 3800 l/min

Flow direction: left ? right

Material seal: NBR

Material housing: Zinc die-cast

Temperature range [°C]: -5 / 50 °C



Pressure range bar	Operating pressure bar	Weight g	Article
0.5 / 12	1 / 16	1480	11645636
0.5 / 12	1 / 16	1090	11645620
0.5 / 12	1 / 16	1860	11645652
0.5 / 12	1 / 16	760	11645604
0.5 / 7	1 / 16	1480	11645634
0.5 / 7	1 / 16	1090	11645618
0.5 / 7	1 / 16	1860	11645650
0.5 / 7	1 / 16	760	11645602
0.5 / 12	1 / 16	1480	11645637
0.5 / 12	1 / 16	760	11645605
0.5 / 12	1 / 16	1860	11645653
0.5 / 12	1 / 16	1090	11645621
0.5 / 7	1 / 16	760	11645603
0.5 / 7	1 / 16	1480	11645635
0.5 / 7	1 / 16	1090	11645619
0.5 / 7	1 / 16	1860	11645651
0.5 / 12		1950	11645608
0.5 / 12		4828	11645656
0.5 / 12		3144	11645624
0.5 / 12		3834	11645640
0.5 / 7		1950	11645606
0.5 / 7		3834	11645638
0.5 / 7		3144	11645622
0.5 / 7		4828	11645654
0.5 / 7	1.5 / 10	500	11649125
0.5 / 7	1.5 / 10	1250	11649128
0.5 / 7	1.5 / 10	750	11649126
0.5 / 7	1.5 / 10	1000	11649127
0.5 / 12		3834	11645641
0.5 / 12		1950	11645609
0.5 / 12		3144	11645625
0.5 / 12		4828	11645657
0.5 / 7		3834	11645639
0.5 / 7		4828	11645655
0.5 / 7		3144	11645623
0.5 / 7		1950	11645607

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.