

FESTO Electric cylinder EPCO

Characteristics

Series: EPCO

Operating temperature: 0 / 50 °C

Degree of protection (IP): 40



Spindle type	Construction size	Stroke length mm	Spindle pitch mm/U	Repetition accuracy mm	Max. feed force Fx N	Article
						12736110
Ball screw	16	50	8	±0,02	50	14166854
Ball screw	16	100	3	±0,02	125	14166859
Ball screw	16	100	8	±0,02	50	14166881
Ball screw	16	150	3	±0,02	125	14166885
Ball screw	16	150	8	±0,02	50	14166906
Ball screw	16	200	3	±0,02	125	14166909
Ball screw	16	200	8	±0,02	50	14166933
Ball screw	25	50	3	±0,02	350	14166827
Ball screw	25	50	10	±0,02	105	14166838
Ball screw	25	100	3	±0,02	350	14166835
Ball screw	25	100	10	±0,02	105	14166849
Ball screw	25	150	3	±0,02	350	14166846
Ball screw	25	150	10	±0,02	105	14166870
Ball screw	25	200	3	±0,02	350	14166867
Ball screw	25	200	10	±0,02	105	14166902
Ball screw	25	300	3	±0,02	350	14166930
Ball screw	25	300	10	±0,02	105	14166961
Ball screw	40	50	5	±0,02	650	14166852
Ball screw	40	50	12.7	±0,02	250	14166896
Ball screw	40	100	5	±0,02	650	14166889
Ball screw	40	100	12.7	±0,02	250	14166926
Ball screw	40	150	5	±0,02	650	14166922
Ball screw	40	150	12.7	±0,02	250	14166954
Ball screw	40	200	5	±0,02	650	14166950
Ball screw	40	200	12.7	±0,02	250	14166969
Ball screw	40	300	5	±0,02	650	14166975
Ball screw	40	300	12.7	±0,02	250	14166985

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.