



FESTO Silencer AMTE

Characteristics

Series: AMTE

Flow rate at 6 Bar l/min	Port thread type	Port Size	Port Size	Port Size in	Noise insulation dB(A)	Article
2.745	BSPP (G)		1/2	92		12645186
10.5	BSPP (G)		1/2	88		12645190
1	BSPP (G)		1/4	95		12645185
3.14	BSPP (G)		1/4	83		12645188
615	BSPP (G)		1/8	92		12645184
1.735	BSPP (G)		1/8	76		12645187
17.235	BSPP (G)		1	88		12645192
12.4	BSPP (G)		3/4	85		12645191
1.545	BSPP (G)		3/8	92		12591329
5.43	BSPP (G)		3/8	82		12645189
95	Metric	M 3		55		12589927
	Metric	M 5		72		23212404
91	Metric	M 5		71		12645183
3.08	NPT		1/4-18	82		13031634
1.615	NPT		1/8-27	77		13031637
5.365	NPT		3/8-18	83		13206523

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.