



FESTO Plastic tubing PEN

Characteristics

Series: PEN

Hose material: Polyethylene

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
2.7	0.75	4	10	50	Black	10	D 52 +/-3	6.43	11649802
2.7	0.75	4	10	500	Black	10	D 52 +/-3	6.43	12264072
2.7	0.75	4	10	500	Blue	10	D 52 +/-3	6.43	12264078
2.7	0.75	4	10	50	Blue	10	D 52 +/-3	6.43	11650836
2.7	0.75	4	10	50	Green	10	D 52 +/-3	6.43	11650848
2.7	0.75	4	10	50	Natural	10	D 52 +/-3	6.43	11649808
2.7	0.75	4	10	50	Red	10	D 52 +/-3	6.43	11650854
2.7	0.75	4	10	50	Silver	10	D 52 +/-3	6.43	11650842
2.7	0.75	4	10	500	Silver				12264083
2.7	0.75	4	10	50	Yellow	10	D 52 +/-3	6.43	11650860
4	1	6	10	500	Black	13.5	D 52 +/-3	14.77	12264073
4	1	6	10	50	Black	13.5	D 52 +/-3	14.77	11649803
4	1	6	10	500	Blue	13.5	D 52 +/-3	14.77	12264079
4	1	6	10	50	Blue	13.5	D 52 +/-3	14.77	11650837
4	1	6	10	50	Green	13.5	D 52 +/-3	14.77	11650849
4	1	6	10	50	Natural	13.5	D 52 +/-3	14.77	11649809
4	1	6	10	50	Red	13.5	D 52 +/-3	14.77	11650855
4	1	6	10	50	Silver	13.5	D 52 +/-3	14.77	11650843
4	1	6	10	500	Silver	13.5	D 52 +/-3	14.77	12264084
4	1	6	10	50	Yellow	13.5	D 52 +/-3	14.77	11650861
5.7	1.25	8	10	50	Black	22.5	D 52 +/-3	23.27	11649804
5.7	1.25	8	10	400	Black	22.5	D 52 +/-3	23.27	12264074
5.7	1.25	8	10	400	Blue	22.5	D 52 +/-3	23.27	12264080
5.7	1.25	8	10	50	Blue	22.5	D 52 +/-3	23.27	11650838
5.7	1.25	8	10	50	Green	22.5	D 52 +/-3	23.27	11650850
5.7	1.25	8	10	50	Natural	22.5	D 52 +/-3	23.27	11649810
5.7	1.25	8	10	50	Red	22.5	D 52 +/-3	23.27	11650856
5.7	1.25	8	10	50	Silver	22.5	D 52 +/-3	23.27	11650844
5.7	1.25	8	10	400	Silver	22.5	D 52 +/-3	23.27	12264085
5.7	1.25	8	10	50	Yellow	22.5	D 52 +/-3	23.27	11650862
7	1.5	10	10	50	Black	23.5	D 52 +/-3	37.66	11649805
7	1.5	10	10	300	Black	23.5	D 52 +/-3	37.66	12264075
7	1.5	10	10	50	Blue	23.5	D 52 +/-3	37.66	11650839
7	1.5	10	10	300	Blue	23.5	D 52 +/-3	37.66	11656900
7	1.5	10	10	50	Green	23.5	D 52 +/-3	37.66	11650851
7	1.5	10	10	50	Natural	23.5	D 52 +/-3	37.66	11649811
7	1.5	10	10	50	Red	23.5	D 52 +/-3	37.66	11650857
7	1.5	10	10	50	Silver	23.5	D 52 +/-3	37.66	11650845
7	1.5	10	10	300	Silver	23.5	D 52 +/-3	37.66	12264086
7	1.5	10	10	50	Yellow	23.5	D 52 +/-3	37.66	11650863
8.4	1.75	12	10	50	Black	33	D 52 +/-3	54.23	11649806

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Internal diameter	Wall thickness	Outer diameter	Maximum operating pressure at 20 °C	Roller length	Colour	Minimum bending radius	Hardness	Weight per meter	Article
mm	mm	mm	bar	m		mm		g	
8.4		12	10	200	Black				12264076
8.4	1.75	12	10	200	Blue	33	D 52 +/-3	54.23	12264081
8.4	1.75	12	10	50	Blue	33	D 52 +/-3	54.23	11650840
8.4	1.75	12	10	50	Green	33	D 52 +/-3	54.23	11650852
8.4	1.75	12	10	50	Natural	33	D 52 +/-3	54.23	11649812
8.4	1.75	12	10	50	Red	33	D 52 +/-3	54.23	11650858
8.4	1.75	12	10	50	Silver	33	D 52 +/-3	54.23	11650846
8.4	1.75	12	10	200	Silver	33	D 52 +/-3	54.23	12264087
8.4	1.75	12	10	50	Yellow	33	D 52 +/-3	54.23	11650864
9.5	2	14	10	50	Black	45	D 52 +/-3	77.3	12266360
9.5	2	14	10	50	Natural	45	D 52 +/-3	77.3	12266361
10.8	2.5	16	10	50	Black	57.5	D 52 +/-3	102.9	11649807
10.8	2.5	16	10	100	Black				12264077
10.8	2.5	16	10	100	Blue	57.5	D 52 +/-3	102.9	12264082
10.8	2.5	16	10	50	Blue	57.5	D 52 +/-3	102.9	11650841
10.8	2.5	16	10	50	Green	57.5	D 52 +/-3	102.9	11650853
10.8	2.5	16	10	50	Natural	57.5	D 52 +/-3	102.9	11649813
10.8	2.5	16	10	50	Red	57.5	D 52 +/-3	102.9	11650859
10.8	2.5	16	10	50	Silver	57.5	D 52 +/-3	102.9	11650847
10.8	2.5	16	10	100	Silver				12264088
10.8	2.5	16	10	50	Yellow	57.5	D 52 +/-3	102.9	11650865

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.