

FESTO Barbed L-Fitting LCNH



Characteristics

Series: LCNH

Operating temperature: 0 / 60 °C

Operating pressure: -0.95 / 10 bar

Manufacturer ID	Material	Connection 1	Connection 2	Nominal size mm	Wrench width mm	Article
LCNH-M5-PK-2	Zinc die-cast / Aluminium	Tubing O.D. 3mm	M5	7	7	11628227
LCNH-1/8-PK-3	Zinc die-cast / Aluminium	Tubing O.D. 4mm	1/8" BSPP[G]	13	13	11628229
LCNH-M5-PK-3	Zinc die-cast / Aluminium	Tubing O.D. 4mm	M5	7	7	11628228
LCNH-1/4-PK-4	Zinc die-cast / Aluminium	Tubing O.D. 6mm	1/4" BSPP[G]	17	17	11628232
LCNH-1/8-PK-4	Zinc die-cast / Aluminium	Tubing O.D. 6mm	1/8" BSPP[G]	13	13	11628230
LCNH-M5-PK-4	Zinc die-cast / Aluminium	Tubing O.D. 6mm	M5	7	7	23212580
LCNH-1/4-PK-6	Zinc die-cast / Aluminium	Tubing O.D. 8mm	1/4" BSPP[G]	17	17	23212581
LCNH-1/8-PK-6	Zinc die-cast / Aluminium	Tubing O.D. 8mm	1/8" BSPP[G]	13	13	11628231
LCNH-3/8-PK-6	Zinc die-cast / Aluminium	Tubing O.D. 8mm	3/8" BSPP[G]	19	19	11628233

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.