

FESTO Elbow fitting NPFC-L



Characteristics

Series: NPFC-L

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Threaded connection 2	Connection 2 thread size	Article
NPFC-L-2M5-M	Brass, Nickel-plated	External thread [M]	M 5	External thread [M]	M 5	12639427
NPFC-L-2R12-M	Brass, Nickel-plated	External thread BSPT [R]	1/2	External thread BSPT [R]	1/2	12639437
NPFC-L-2R14-M	Brass, Nickel-plated	External thread BSPT [R]	1/4	External thread BSPT [R]	1/4	12639444
NPFC-L-2R18-M	Brass, Nickel-plated	External thread BSPT [R]	1/8	External thread BSPT [R]	1/8	12639452
NPFC-L-2R34-M	Brass, Nickel-plated	External thread BSPT [R]	3/4	External thread BSPT [R]	3/4	12639457
NPFC-L-2R38-M	Brass, Nickel-plated	External thread BSPT [R]	3/8	External thread BSPT [R]	3/8	12639465
NPFC-L-2M5-MF	Brass, Nickel-plated	Internal thread [M]	M 5	External thread [M]	M 5	12639426
NPFC-L-2M5-F	Brass, Nickel-plated	Internal thread [M]	M 5	Internal thread [M]	M 5	12639424
NPFC-L-R12-G12-MF	Brass, Nickel-plated	Internal thread BSPP [G]	1/2	External thread BSPT [R]	1/2	12639361
NPFC-L-2G12-F	Brass, Nickel-plated	Internal thread BSPP [G]	1/2	Internal thread BSPP [G]	1/2	12639342
NPFC-L-R14-G14-MF	Brass, Nickel-plated	Internal thread BSPP [G]	1/4	External thread BSPT [R]	1/4	12639377
NPFC-L-2G14-F	Brass, Nickel-plated	Internal thread BSPP [G]	1/4	Internal thread BSPP [G]	1/4	12639366
NPFC-L-R18-G18-MF	Brass, Nickel-plated	Internal thread BSPP [G]	1/8	External thread BSPT [R]	1/8	12639395
NPFC-L-2G18-F	Brass, Nickel-plated	Internal thread BSPP [G]	1/8	Internal thread BSPP [G]	1/8	12639383
NPFC-L-R1-G1-MF	Brass, Nickel-plated	Internal thread BSPP [G]	1	External thread BSPT [R]	1	12639341
NPFC-L-2G1-F	Brass, Nickel-plated	Internal thread BSPP [G]	1	Internal thread BSPP [G]	1	12639339
NPFC-L-R34-G34-MF	Brass, Nickel-plated	Internal thread BSPP [G]	3/4	External thread BSPT [R]	3/4	12639407
NPFC-L-2G34-F	Brass, Nickel-plated	Internal thread BSPP [G]	3/4	Internal thread BSPP [G]	3/4	12639403
NPFC-L-R38-G38-MF	Brass, Nickel-plated	Internal thread BSPP [G]	3/8	External thread BSPT [R]	3/8	12639419
NPFC-L-2G38-F	Brass, Nickel-plated	Internal thread BSPP [G]	3/8	Internal thread BSPP [G]	3/8	12639411

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.