



FESTO Elbow quick connector LCK

Characteristics

Series: LCK

Operating temperature: -10 / 60 °C

Operating pressure: 0 / 16 bar

Manufacturer ID	Material	Connection 1	Connection 1 mm	Connection 2	Connection 2 mm	Nominal size mm	Wrench width mm	Wrench width 2 mm	Article
LCK-1/8-PK-3	Zinc die-cast	CK connection 3mm	1/8" BSPP(G)	13	13	8			23212564
LCK-M5-PK-3	Zinc die-cast	CK connection 3mm	M5	7	7	8			23212398
LCK-1/4-PK-4	Zinc die-cast	CK connection 4mm	1/4" BSPP(G)	17	17	12			23212401
LCK-1/8-PK-4	Zinc die-cast	CK connection 4mm	1/8" BSPP(G)	13	13	12			23212399
LCK-M5-PK-4	Zinc die-cast	CK connection 4mm	M5	7	7	8			11345195
LCK-1/4-PK-6	Zinc die-cast	CK connection 6mm	1/4" BSPP(G)	17	17	14			23212402
LCK-1/8-PK-6	Zinc die-cast	CK connection 6mm	1/8" BSPP(G)	13	13	14			23212400
LCK-1/4-PK-9	Zinc die-cast	CK connection 9mm	1/4" BSPP(G)	17	17	19			23212565
LCK-3/8-PK-9	Zinc die-cast	CK connection 9mm	3/8" BSPP(G)	22	22	19			23212567
LCK-1/2-PK-13	Zinc die-cast	CK connection 13mm	1/2" BSPP(G)	27	27	24			23212568
LCK-1/4-PK-4-KU	POM	CK connection 4mm	1/4" BSPP(G)	17	17	12			23212571
LCK-1/8-PK-4-KU	POM	CK connection 4mm	1/8" BSPP(G)	13	13	12			23212569
LCK-1/4-PK-6-KU	POM	CK connection 6mm	1/4" BSPP(G)	17	17	14			23212572
LCK-1/8-PK-6-KU	POM	CK connection 6mm	1/8" BSPP(G)	13	13	14			23212570

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.