



FESTO Mini slide EGSL

Characteristics

Series: EGSL

Operating temperature: 0 / 60 °C

Degree of protection (IP): 40

Spindle type	Construction size	Stroke length mm	Spindle pitch mm/U	Repetition accuracy mm	Max. feed force Fx N	Article
Ball screw	35	50	8	±0.015	75	12265365
Ball screw	45	100	3	±0.015	150	12265370
Ball screw	45	100	10	±0.015	150	12265062
Ball screw	45	200	3	±0.015	150	12265371
Ball screw	45	200	10	±0.015	150	12265063
Ball screw	55	100	5	±0.015	300	12265372
Ball screw	55	100	12.7	±0.015	300	12265064
Ball screw	55	200	5	±0.015	300	12265373
Ball screw	55	200	12.7	±0.015	300	12265065
Ball screw	55	250	5	±0.015	300	12265374
Ball screw	55	250	12.7	±0.015	300	12265066
Ball screw	75	100	10	±0.015	450	12265375
Ball screw	75	100	20	±0.015	450	12265067
Ball screw	75	200	10	±0.015	450	12265376
Ball screw	75	200	20	±0.015	450	12265068
Ball screw	75	300	10	±0.015	450	12265377
Ball screw	75	300	20	±0.015	450	12265069

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.