



FESTO Mini slide SLF

Characteristics

- Series:** SLF
- Function:** Double acting
- Housing material:** Aluminium alloy
- Operating temperature:** -20 / 60 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	mm	bar	
SLF-6-10-P-A	Mechanical	6	10	M 5	1.5 / 10	11633383
SLF-6-20-P-A	Mechanical	6	20	M 5	1.5 / 10	11633384
SLF-6-30-P-A	Mechanical	6	30	M 5	1.5 / 10	11633385
SLF-10-10-P-A	Mechanical	10	10	M 5	1 / 10	11633386
SLF-10-20-P-A	Mechanical	10	20	M 5	1 / 10	11633387
SLF-10-30-P-A	Mechanical	10	30	M 5	1 / 10	11633388
SLF-10-40-P-A	Mechanical	10	40	M 5	1 / 10	11633389
SLF-10-50-P-A	Mechanical	10	50	M 5	1 / 10	11633390
SLF-16-10-P-A	Mechanical	16	10	M 5	1 / 10	11633391
SLF-16-20-P-A	Mechanical	16	20	M 5	1 / 10	11633392
SLF-16-30-P-A	Mechanical	16	30	M 5	1 / 10	11633393
SLF-16-40-P-A	Mechanical	16	40	M 5	1 / 10	11633394
SLF-16-50-P-A	Mechanical	16	50	M 5	1 / 10	11633395
SLF-16-80-P-A	Mechanical	16	80	M 5	1 / 10	11633396

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.