

FESTO Proximity sensor SDBT



Characteristics

Series: SDBT
Construction type housing: For T-slot
Measurement principle: Magnetostrictive

Manufacturer ID	Operating voltage at DC V	Type of switching output	Type of switch function	Electrical connection	Article
SDBT-MS-20NL-ZN-E-10-LE-EX6	7.5 / 18	NAMUR	NAMUR	Cable, 2-wire open end	14429775
SDBT-MS-20NL-ZN-E-5-LE-EX6	7.5 / 18	NAMUR	NAMUR	Cable, 2-wire open end	13400540
SDBT-BSW-1L-ZU-W-5-N-LE	10 / 30	Non-contacting 2-wire	Normally open contact [NO]	Cable, 2-wire open end	14168891
SDBT-BSW-1L-NU-W-5-N-LE	10 / 30	NPN	Normally open contact [NO]	Cable 3-wire open end	14168896
SDBT-BSW-1L-NU-W-0.3-N-M12	10 / 30	NPN	Normally open contact [NO]	Cable with plug, M12x1, 3-pin	14168895
SDBT-BSW-1L-PU-W-0.3-N-M12	10 / 30	PNP	Normally open contact [NO]	Cable with plug, M12x1, 3-pin	14168897
	10	PNP/NPN			14525982
	10	PNP/NPN			14525985
	10	PNP/NPN		Cable 3-wire open end	14525986
	10	PNP/NPN		Cable 3-wire open end	14525983
	10	PNP/NPN		Cable 3-wire open end	14525984

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.