

FESTO Proximity sensor SME-10M



Characteristics

- Series:** SME-10M
- Construction type housing:** For round slot
- Measurement principle:** Reed magnetic

Manufacturer ID	Operating voltage at DC V	Type of switching output	Type of switch function	Electrical connection	Article
SME-10M-DS-24V-E-2,5-L-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable 3-wire open end	12264035
SME-10M-DS-24V-E-2,5-Q-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable 3-wire open end	12264036
SME-10M-DS-24V-E-0,3-L-M8D	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable with plug, M8x1, 3-pin	12264037
SME-10M-DS-24V-E-0,3-Q-M8D	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable with plug, M8x1, 3-pin	12264038
SME-10M-ZS-24V-E-2,5-L-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable, 2-wire open end	12264039
SME-10M-ZS-24V-E-2,5-Q-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable, 2-wire open end	12264040

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.