

FESTO Proximity sensor SME-8M



Characteristics

Series: SME-8M
Construction type housing: For T-slot
Measurement principle: Reed magnetic

Manufacturer ID	Operating voltage at DC V	Type of switching output	Type of switch function	Electrical connection	Article
SME-8M-DS-24V-K-5,0-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable 3-wire open end	11650035
SME-8M-DS-24V-K-7,5-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable 3-wire open end	11650047
SME-8M-DS-24V-K-2,5-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable 3-wire open end	11650034
SME-8M-ZS-24V-K-2,5-OE	5 / 30	with contact, bipolar	Normally open contact [NO]	Cable, 2-wire open end	11650044
SME-8M-DO-24V-K-7,5-OE	5 / 30	with contact, bipolar	Breaker contact [NC]	Cable, 3-core	12263328
SME-8M-DS-24V-K-0,3-M8D	5 / 30	with contact, bipolar	Normally open contact [NO]	Plug, M8x1, 3-pin	11650033

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.