

FESTO Standard cylinder DNC



Characteristics

Series: DNC

Function: Double acting

Magnetic: Yes

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
DNC-40-50-PPV	Adjustable	40	50	G1/4	0.6 / 12	11632693
DNC-32-20-PPV-A	Adjustable	32	20	G1/8	0.6 / 12	14486745
DNC-32-150-PPV-A	Adjustable	32	150	G1/8	0.6 / 12	14486735
DNC-40-20-PPV-A	Adjustable	40	20	G1/4	0.6 / 12	14486747
DNC-40-30-PPV-A	Adjustable	40	30	G1/4	0.6 / 12	14486746
DNC-40-70-PPV-A	Adjustable	40	70	G1/4	0.6 / 12	14486762
DNC-50-20-PPV-A	Adjustable	50	20	G1/4	0.6 / 12	14486749
DNC-50-30-PPV-A	Adjustable	50	30	G1/4	0.6 / 12	14486763
DNC-63-20-PPV-A	Adjustable	63	20	G3/8	0.6 / 12	14486765
DNC-63-40-PPV-A	Adjustable	63	40	G3/8	0.6 / 12	14486766
DNC-63-70-PPV-A	Adjustable	63	70	G3/8	0.6 / 12	14486768
DNC-63-150-PPV-A	Adjustable	63	150	G3/8	0.6 / 12	14486750
DNC-80-20-PPV-A	Adjustable	80	20	G3/8	0.6 / 12	14486769
DNC-80-30-PPV-A	Adjustable	80	30	G3/8	0.6 / 12	14486737
DNC-80-60-PPV-A	Adjustable	80	60	G3/8	0.6 / 12	14486774
DNC-80-70-PPV-A	Adjustable	80	70	G3/8	0.6 / 12	14486775
DNC-80-150-PPV-A	Adjustable	80	150	G3/8	0.6 / 12	14486736
DNC-125-100-PPV-A	Adjustable	125	100	G1/2	0.6 / 10	11632755

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.