



FESTO Parallel gripper DHPS

Characteristics

Series: DHPS

Operating temperature: 5 / 60 °C

Manufacturer ID	Bore diameter mm	Operation	Stroke length mm	Connection	Total force at 6 bar, closing N	Total force at 6 bar, opening N	Operating pressure bar	Article
DHPS-6-A	6	Double acting	2	M3	25	30	2 / 8	12267040
DHPS-10-A-NC	10	Double acting	3	M3			4 / 8	12267043
DHPS-10-A-NO	10	Double acting	3	M3			4 / 8	12267042
DHPS-10-A	10	Double acting	3	M3	70	80	2 / 8	12267041
DHPS-16-A	16	Double acting	5	M3	190	210	2 / 8	12267044
DHPS-16-A-NO	16	Double acting	5	M3			4 / 8	12267045
DHPS-16-A-NC	16	Double acting	5	M3			4 / 8	12267046
DHPS-20-A-NC	20	Double acting	6.5	M5			4 / 8	12267049
DHPS-20-A-NO	20	Double acting	6.5	M5			4 / 8	12267048
DHPS-20-A	20	Double acting	6.5	M5	290	320	2 / 8	12267047
DHPS-25-A	25	Double acting	7.5	G1/8	450	500	2 / 8	12267050
DHPS-25-A-NC	25	Double acting	7.5	G1/8			4 / 8	12267052
DHPS-25-A-NO	25	Double acting	7.5	G1/8			4 / 8	12267051
DHPS-35-A-NC	35	Double acting	12.5	G1/8			4 / 8	12267055
DHPS-35-A-NO	35	Double acting	12.5	G1/8			4 / 8	12267054
DHPS-35-A	35	Double acting	12.5	G1/8	910	970	2 / 8	12267053

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.