

FESTO Spindle axis ELGC



Characteristics

Series: ELGC

Operating temperature: 0 / 50 °C

Degree of protection (IP): 40

Spindle type	Construction size	Stroke length mm	Spindle pitch mm/U	Repetition accuracy mm	Max. feed force Fx N	Article
						14170145
Ball screw	32	100	8	±0.015	40	14170124
Ball screw	32	200	8	±0.015	40	14170127
Ball screw	32	300	8	±0.015	40	14170129
Ball screw	32	400	8	±0.015	40	14170133
Ball screw	32	500	8	±0.015	40	14170136
Ball screw	32	600	8	±0.015	40	14170139
Ball screw	32	800	8	±0.015	40	14170143
Ball screw	45	100	10	±0.015	100	14170123
Ball screw	45	300	10	±0.015	100	14170125
Ball screw	45	400	10	±0.015	100	14170128
Ball screw	45	500	10	±0.015	100	14170131
Ball screw	45	600	10	±0.015	100	14170134
Ball screw	45	800	10	±0.015	100	14170140
Ball screw	60	100	12	±0.01	200	14170126
Ball screw	60	200	12	±0.01	200	14170130
Ball screw	60	300	12	±0.01	200	14170135
Ball screw	60	400	12	±0.01	200	14170138
Ball screw	60	500	12	±0.01	200	14170142
Ball screw	60	600	12	±0.01	200	14170144
Ball screw	60	800	12	±0.01	200	14170147
Ball screw	80	100	16	±0.01	350	14170132
Ball screw	80	200	16	±0.01	350	14170137
Ball screw	80	300	16	±0.01	350	14170141
Ball screw	80	500	16	±0.01	350	14170146
Ball screw	80	600	16	±0.01	350	14170148
Ball screw	80	800	16	±0.01	350	14170149
Ball screw	80	1000	16	±0.01	350	14170150

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.