



FESTO Stopper cylinder double acting DFST

Characteristics

Series: DFST

Function: Double acting

Magnetic: Yes

Housing material: Aluminium alloy

Operating temperature: 5 / 60 °C

Manufacturer ID	Cushioning	Bore diameter mm	Stroke length mm	Port Size in	Operating pressure bar	Article
						14167844
DFST-32-20-D-Y4-A-G2	Shock absorber	32	20	G1/8	2 / 10	14086421
DFST-32-20-DL-Y4-A-G2	Shock absorber	32	20	G1/8	2 / 10	14086425
DFST-32-20-D-Y4-A-S-G2	Shock absorber	32	20	G1/8	2 / 10	14086422
DFST-32-20-DL-Y4-A-S-G2	Shock absorber	32	20	G1/8	2 / 10	14086426
DFST-50-30-D-Y4-A-S-G2	Shock absorber	50	30	G1/8	2 / 10	14086398
DFST-50-30-D-Y4-A-G2	Shock absorber	50	30	G1/8	2 / 10	14086397
DFST-50-30-DL-Y4-A-S-G2	Shock absorber	50	30	G1/8	2 / 10	14086400
DFST-50-30-DL-Y4-A-G2	Shock absorber	50	30	G1/8	2 / 10	14086399
DFST-63-30-D-Y4-A-S-G2	Shock absorber	63	30	G1/8	2 / 10	14086404
DFST-63-30-D-Y4-A-G2	Shock absorber	63	30	G1/8	2 / 10	14086403
DFST-63-30-DL-Y4-A-G2	Shock absorber	63	30	G1/8	2 / 10	14086407
DFST-63-30-DL-Y4-A-S-G2	Shock absorber	63	30	G1/8	2 / 10	14086408
DFST-80-40-DL-Y4-A-S-G2	Shock absorber	80	40	G1/8	2 / 10	14086416
DFST-80-40-D-Y4-A-G2	Shock absorber	80	40	G1/8	2 / 10	14086411
DFST-80-40-D-Y4-A-S-G2	Shock absorber	80	40	G1/8	2 / 10	14086412
DFST-80-40-DL-Y4-A-G2	Shock absorber	80	40	G1/8	2 / 10	14086415

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.