


FESTO Toothed belt axis EGC



Characteristics

Series: EGC

Operating temperature: -10 / 60 °C

Degree of protection (IP): 40

Construction size	Stroke length	Repetition accuracy	Max. feed force Fx	Article
	mm	mm	N	
70	300	±0.08	100	14170397
70	400	±0.08	100	14170398
70	500	±0.08	100	14170399
70	600	±0.08	100	14170400
70	800	±0.08	100	14170401
70	1000	±0.08	100	14170404
70	1200	±0.08	100	14170408
80	400	±0.08	350	14170402
80	500	±0.08	350	14170403
80	600	±0.08	350	14170406
80	800	±0.08	350	14170409
80	1000	±0.08	350	14170411
80	1200	±0.08	350	14170413
120	400	±0.08	800	14170417
120	500	±0.08	800	14170420
120	600	±0.08	800	14170421
120	800	±0.08	800	14170423
120	1000	±0.08	800	14170425
120	1200	±0.08	800	14170426
120	1500	±0.08	800	14170430

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.