



FESTO T-Fitting NPFC

Characteristics

Series: NPFC

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size	Connection 1 thread size in	Threaded connection 2	Connection 2 thread size	Connection 2 thread size in	Article
NPFC-T-2R18-G18-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8			12639454
NPFC-T-R18-2G18-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8			12639396
NPFC-T-3R14-M	Brass, Nickel-plated	External thread BSPT (R)	1/4					12639447
NPFC-T-2R14-G14-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4			12639446
NPFC-T-R14-2G14-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4			12639378
NPFC-T-3R38-M	Brass, Nickel-plated	External thread BSPT (R)	3/8					12639467
NPFC-T-R38-2G38-MFF	Brass, Nickel-plated	External thread BSPT (R)	3/8	Internal thread BSPP (G)	3/8			12639420
NPFC-T-3R12-M	Brass, Nickel-plated	External thread BSPT (R)	1/2					12639439
NPFC-T-2R12-G12-MMF	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2			12639435
NPFC-T-R12-2G12-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2			12639362
NPFC-T-3M5-MFF	Brass, Nickel-plated	Internal thread (M)	M 5	External thread (M)	M 5			14170551
NPFC-T-3M5-FMF	Brass, Nickel-plated	Internal thread (M)	M 5	External thread (M)	M 5			12639428
NPFC-T-3G18-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/8					12639385
NPFC-T-2G18-R18-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/8	External thread BSPT (R)	1/8			12639449
NPFC-T-G18-2R18-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	1/8	External thread BSPT (R)	1/8			12639450
NPFC-T-3G14-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/4					12639369
NPFC-T-G14-2R14-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	External thread BSPT (R)	1/4			12639442
NPFC-T-2G14-R14-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/4	External thread BSPT (R)	1/4			12639441
NPFC-T-3G38-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/8					12639414
NPFC-T-2G38-R38-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	External thread BSPT (R)	3/8			12639459
NPFC-T-G38-2R38-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	3/8	External thread BSPT (R)	3/8			12639460
NPFC-T-G12-2R12-FMM	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	External thread BSPT (R)	1/2			12639433
NPFC-T-2G12-R12-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1/2	External thread BSPT (R)	1/2			12639434
NPFC-T-3G34-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/4					12639406
NPFC-T-2G34-R34-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	3/4	External thread BSPT (R)	3/4			12639456
NPFC-T-3G1-F	Brass, Nickel-plated	Internal thread BSPP (G)	1					12639340
NPFC-T-2G1-R1-FMF	Brass, Nickel-plated	Internal thread BSPP (G)	1	External thread BSPT (R)	1			12639431

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.