



FESTO Y-Fitting NPFC

Characteristics

Series: NPFC

Ambient temperature: -20 / 150 °C

Operating pressure: -0.95 / 50 bar

Manufacturer ID	Material	Threaded connection 1	Connection 1 thread size in	Threaded connection 2	Connection 2 thread size in	Article
NPFC-Y-R18-2G18-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/8	Internal thread BSPP (G)	1/8	12639386
NPFC-Y-R14-2G14-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/4	Internal thread BSPP (G)	1/4	12639372
NPFC-Y-R38-2G38-MFF	Brass, Nickel-plated	External thread BSPT (R)	3/8	Internal thread BSPP (G)	3/8	12639417
NPFC-Y-R12-2G12-MFF	Brass, Nickel-plated	External thread BSPT (R)	1/2	Internal thread BSPP (G)	1/2	12639358
NPFC-Y-3G14-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/4			12639368
NPFC-Y-3G38-F	Brass, Nickel-plated	Internal thread BSPP (G)	3/8			12639413
NPFC-Y-3G12-F	Brass, Nickel-plated	Internal thread BSPP (G)	1/2			12639354

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.