



TA Regulating valve Series: TA-Modulator Type: 26293 Dynamic AMETAL External thread (BSPP)

Characteristics

- Series:** TA-Modulator
- Type:** 26293
- Housing material:** AMETAL
- Connection:** External thread (BSPP)
- Type of control gear:** Dynamic
- Application:** CH water
- With measuring nipples:** Yes
- Minimum medium temperature (continuous):** -20 °C
- Maximum medium temperature (continuous):** 90 °C

Application

- Recommended in: Utilities

Nominal inner diameter	Pressure rating	Control range l/h	Kvs value m³/h	Kv value m³/h	Article
3/4" [20]	PN16	90 / 480	0.48	0.09 / 0.48	13389148
1" [25]	PN16	200 / 980	0.98	0.2 / 0.98	13342871
1.1/4" [32]	PN16	340 / 1750	1.75	0.34 / 1.75	13463570
1.1/2" [40]	PN16	720 / 3600	3.6	0.72 / 3.6	13463571

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.