



ARI Globe valve Type 2876 series 12.405 cast iron electric flange EN (DIN) PN16

Characteristics

Function: Two-way valve
Norm: EN (DIN)
Construction type: Straight
Housing material: Cast iron
Material quality: EN-JL1040
Process connection: Flange
Standard connection: EN 1092-2
Flange finish: Raised face
Face to Face norm: EN 558, Series 1
Type of disc: Fixed disc
Max. pressure difference in opened position: 2 bar
Actuation: Pressure below the valve
Type of actuator: Electrical
Function actuator: Last position
Position indicator: Yes
Emergency manual operation: Yes
Stem seal type: Roof cuffs
Primary spindle seal material: PTFE
Material disc: 1.4021+QT
Seat material: 1.4021+QT
Spindle material: 1.4021+QT
Material bonnet: EN-JS1049

Bonnet gasket material: Graphite
Surface protection: Paint min. 30 µm
Actuator material: PC
Level of protection (IP value): IP65
Medium temperature: -10 / 220 °C

Application

- Water.
- Warm and hot water.
- Groundwater
- Steam.
- Refrigerant.
- Neutral liquids and gases.

Technical Information

- Electric actuator.
- Economical thanks to compact design.

Options

- Different seal variants.
- PTFE valve ring for even better sealing.

Size process connection	Pressure rating	Kv value m³/h	Closing pressure bar	Type coding actuator	Supply voltage	Adjusting force kN	Max. electric power input W	Operating time	End contacts	Article
DN15	PN16	4.2	16	Premio 2,2	230V AC	2.2	21	11s	No	13417285
DN25	PN16	12	16	Premio 2,2	230V AC	2.2	21	18s	No	13250476
DN32	PN16	19	14.8	Premio 2,2	230V AC	2.2	21	21s	No	13417284
DN40	PN16	31	7.1	Premio 2,2	230V AC	2.2	21	26s	No	13417286
DN50	PN16	47	15.9	Premio 5	100 -240V AC	5	65	13s / 28s / 34s 2 x 10A / 52s / 250V AC		13288305

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.