




AFLEX Hose Corroline Plus AS, very flexible antistatic PTFE hose with a smooth bore and black EPDM cover



Application

- very flexible, antistatic PTFE suction and delivery hose with EPDM outer cover
- suitable for the chemical industry
- not suitable for continuous operation with steam
- the unique patented design makes the hose smooth on the inside, very flexible and virtually kink-resistant
- can be installed in short sections, as the flow rate is guaranteed even with a very small bending radius
- the design ensures a higher flow rate and a lower pressure drop than with a corrugated PTFE hose
- Recommended in: Food & Beverages

Technical Information

Temperature range

- -40 °C to +150 °C
- for autoclave cleaning, a maximum temperature of 135 °C applies for at least 100 x 30 minutes

Burst pressure

- safety factor 4:1

Test pressure

- 1.5 x maximum operating pressure

Vacuum resistance

- 90% to 150 °C

Construction

Inner wall

- black antistatic PTFE
- smooth, seamless inner wall, phthalate-free
- "rib" profile on the outside

Reinforcement

- stainless steel spiral AISI 316 in the spiral recess
- stainless steel braiding AISI 316

Outer cover

- black antistatic EPDM with integrated steel spiral
- fire-resistant

Execution

Couplings

- PTFE crimping or hydraulically pressed

Approval

Standards/approvals

- EC1935/2004 - EU 10/2011 A,B,C,D1,D2,E
- 2014/34/EU
- EN 16643

Options

Options

- image is for illustration purposes only
- pressure test report
- clearly visible laser engraving on rotatable sleeve

Description	Article
Hose webshop Corroline+ AS DN25 2x47C	13175419
Hose webshop Corroline+ AS DN25 2xDBW	13175418

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.