




AFLEX Hose Corroflon AS, corrugated PTFE hose with spiral and stainless steel braiding



Application

- very flexible, corrugated PTFE suction and delivery hose with stainless steel braiding
- suitable for the chemical, pharmaceutical and foodstuff industries
- the unique patented design makes the hose very flexible, kink-resistant and also easy to clean on the inside
- can be installed in short sections thanks to the small bending radius
- Recommended in: Food & Beverages, Pharma



Technical Information

Temperature range

- -73 °C to +260 °C

Burst pressure

- see table under "Tables"

Test pressure

- 1.5 x maximum operating pressure

Vacuum resistance*

- 90% to 150 °C to including 2"
- *) to 150 °C; At temperatures > 150 °C, the vacuum resistance decreases by 1% for every 1 °C that the temperature increases.

Construction

Inner wall

- black antistatic PTFE
- spiral-wound, seamless, phthalate-free

Reinforcement

- stainless steel spiral AISI 304

Outer cover

- stainless steel braiding AISI 304

Execution

Couplings

- PTFE crimping or hydraulically and hygienically pressed

Approval

Standards/approvals

- EC1935/2004 - EU 10/2011 A,B,C,D1,D2,E
- 2014/34/EU
- FDA 21 CFR 178.3297
- USP VI

Options

Other versions

- Corroflon AS PB: black antistatic PTFE with black PP braiding (up to 100 °C)
- Corroflon AS RC: black antistatic PTFE with black, antistatic and fire-resistant EPDM coating (up to 150 °C)
- Corroflon AS SI: black antistatic PTFE with silicone coating (up to 224 °C)
- Corroflon AS RC Blue: black antistatic PTFE with blue EPDM coating (up to 150 °C)

Options

- image is for illustration purposes only
- hoses with Hastelloy braiding available on request
- hoses with PTFE design in white available on request
- available with full-length stainless-steel protective spiral
- fire-resistant design
- pressure test report
- clearly visible laser engraving on rotatable sleeve

Description	Article
Hose webshop Corroflon AS DN25 2x47C	13175420
Hose webshop Corroflon AS DN25 2xDBW	13175421

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.