


EWELLIX Linear actuator DC version series CAHB-10



Characteristics

Series: CAHB-10

Temperature range: -40 / 85 °C

Manufacturer ID	Type of drive	Stroke mm	Speed mm/s	Nominal voltage V	Nominal current A	Protection class	Article
CAHB-10- B5A-050158- AAAA0A-000	Trapezoidal screw	50	8	24	1.6	IP66s/69k	13686796
CAHB-10- B3A-050158- AAAA0A-000	Trapezoidal screw	50	16	24	1.8	IP66s/69k	13686793
CAHB-10- B2A-050158- AAAA0A-000	Trapezoidal screw	50	30	24	2	IP66s/69k	13686790
CAHB-10- B1A-050158- ABBA0D-000	Trapezoidal screw	50	56	24	2.2	IP66s/69k	13382164
CAHB-10- B3A-100209- AAAA0A-000	Trapezoidal screw	100	16	24	1.8	IP66s/69k	13686794
CAHB-10- B2A-100209- AAAA0A-000	Trapezoidal screw	100	30	24	2	IP66s/69k	13686791
CAHB-10- B5A-300413- AAAA0A-000	Trapezoidal screw	300	8	24	1.6	IP66s/69k	13686797
CAHB-10- B3A-300413- AAAA0A-000	Trapezoidal screw	300	16	24	1.8	IP66s/69k	13686795
CAHB-10- B2A-300413- AAAA0A-000	Trapezoidal screw	300	30	24	2	IP66s/69k	13686792

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.