



GRUNDFOS CRN series vertical multistage AISI 316 centrifugal pumps - PJE

Characteristics

Series: CRN

Material pump casing: Stainless steel

Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
1.8	1.4408	42.2 mm	-20 / 120	23502384
1.8	1.4408	42.2 mm	-20 / 120	23501963
1.8	1.4408	42.2 mm	-20 / 120	23501960
1.8	1.4408	42.2 mm	-20 / 120	23501957
1.8	1.4408	42.2 mm	-20 / 120	23501955
1.8	1.4408	42.2 mm	-20 / 120	23502385
1.8	1.4408	42.2 mm	-20 / 120	23501969
1.8	1.4408	42.2 mm	-20 / 120	23501952
1.8	1.4408	42.2 mm	-20 / 120	23501961
1.8	1.4408	42.2 mm	-20 / 120	23501966
1.8	1.4408	42.2 mm	-20 / 120	23501958
1.8	1.4408	42.2 mm	-20 / 120	23501964
1.8	1.4408	42.2 mm	-20 / 120	23501970
1.8	1.4408	42.2 mm	-20 / 120	23501950
1.8	1.4408	42.2 mm	-20 / 120	23501953
1.8	1.4408	42.2 mm	-20 / 120	23501959
1.8	1.4408	42.2 mm	-20 / 120	23501962
1.8	1.4408	42.2 mm	-20 / 120	23501965
1.8	1.4408	42.2 mm	-20 / 120	23501971
1.8	1.4408	42.2 mm	-20 / 120	23501968
1.8	1.4408	42.2 mm	-20 / 120	23501951
1.8	1.4408	42.2 mm	-20 / 120	23501954
1.8	1.4408	42.2 mm	-20 / 120	23501967
1.8	1.4408	42.2 mm	-20 / 120	23501956
1.8	1.4408	DN25 - DN32	-20 / 120	23501932
3	1.4408	42.2 mm	-20 / 120	23502033
3	1.4408	42.2 mm	-20 / 120	23502411
3	1.4408	42.2 mm	-20 / 120	23502036
3	1.4408	42.2 mm	-20 / 120	23501469
3	1.4408	42.2 mm	-20 / 120	23502039
3	1.4408	42.2 mm	-20 / 120	23501848
3	1.4408	42.2 mm	-20 / 120	23501088
3	1.4408	42.2 mm	-20 / 120	23502030
3	1.4408	42.2 mm	-20 / 120	23502041
3	1.4408	42.2 mm	-20 / 120	23502407
3	1.4408	42.2 mm	-20 / 120	23501847
3	1.4408	42.2 mm	-20 / 120	23502035
3	1.4408	42.2 mm	-20 / 120	23502038
3	1.4408	42.2 mm	-20 / 120	23502409
3	1.4408	42.2 mm	-20 / 120	23502410
3	1.4408	42.2 mm	-20 / 120	23502029
3	1.4408	42.2 mm	-20 / 120	23502040
3	1.4408	42.2 mm	-20 / 120	23502031

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
3	1.4408	42.2 mm	-20 / 120	23502037
3	1.4408	42.2 mm	-20 / 120	23502034
3	1.4408	42.2 mm	-20 / 120	23501849
3	1.4408	42.2 mm	-20 / 120	23502028
3	1.4408	42.2 mm	-20 / 120	23502042
3	1.4408	42.2 mm	-20 / 120	23501258
3	1.4408	42.2 mm	-20 / 120	23502408
3	1.4408	42.2 mm	-20 / 120	23502043
3	1.4408	42.2 mm	-20 / 120	23502032
3	1.4408	42.2 mm	-20 / 120	23501225
5.8	1.4408	42.2 mm	-20 / 120	23502433
5.8	1.4408	42.2 mm	-20 / 120	23501858
5.8	1.4408	42.2 mm	-20 / 120	23502090
5.8	1.4408	42.2 mm	-20 / 120	23501851
5.8	1.4408	42.2 mm	-20 / 120	23502422
5.8	1.4408	42.2 mm	-20 / 120	23501857
5.8	1.4408	42.2 mm	-20 / 120	23502093
5.8	1.4408	42.2 mm	-20 / 120	23502429
5.8	1.4408	42.2 mm	-20 / 120	23502088
5.8	1.4408	42.2 mm	-20 / 120	23502096
5.8	1.4408	42.2 mm	-20 / 120	23502099
5.8	1.4408	42.2 mm	-20 / 120	23502423
5.8	1.4408	42.2 mm	-20 / 120	23502426
5.8	1.4408	42.2 mm	-20 / 120	23501852
5.8	1.4408	42.2 mm	-20 / 120	23502432
5.8	1.4408	42.2 mm	-20 / 120	23502427
5.8	1.4408	42.2 mm	-20 / 120	23502097
5.8	1.4408	42.2 mm	-20 / 120	23502424
5.8	1.4408	42.2 mm	-20 / 120	23502094
5.8	1.4408	42.2 mm	-20 / 120	23502091
5.8	1.4408	42.2 mm	-20 / 120	23502092
5.8	1.4408	42.2 mm	-20 / 120	23502100
5.8	1.4408	42.2 mm	-20 / 120	23502095
5.8	1.4408	42.2 mm	-20 / 120	23502430
5.8	1.4408	42.2 mm	-20 / 120	23501853
5.8	1.4408	42.2 mm	-20 / 120	23502089
5.8	1.4408	42.2 mm	-20 / 120	23501850
5.8	1.4408	42.2 mm	-20 / 120	23502425
5.8	1.4408	42.2 mm	-20 / 120	23502087
5.8	1.4408	42.2 mm	-20 / 120	23502098
5.8	1.4408	42.2 mm	-20 / 120	23502428
5.8	1.4408	42.2 mm	-20 / 120	23501854
5.8	1.4408	42.2 mm	-20 / 120	23502431
5.8	1.4408	42.2 mm	-20 / 120	23501218
5.8	1.4408	42.2 mm	-20 / 120	23502434
10	1.4408	60.1 mm	-20 / 120	23501379
10	1.4408	60.1 mm	-20 / 120	23501328
10	1.4408	60.1 mm	-20 / 120	23501382
10	1.4408	60.1 mm	-20 / 120	23501351
10	1.4408	60.1 mm	-20 / 120	23501353
10	1.4408	60.1 mm	-20 / 120	23501384
10	1.4408	60.1 mm	-20 / 120	23501348
10	1.4408	60.1 mm	-20 / 120	23501381

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Nominal volume flow rate m³/h	Material quality	Nominal inner diameter	Medium temperature °C	Article
10	1.4408	60.1 mm	-20 / 120	23501386
10	1.4408	60.1 mm	-20 / 120	23501350
10	1.4408	60.1 mm	-20 / 120	23501326
10	1.4408	60.1 mm	-20 / 120	23501349
10	1.4408	60.1 mm	-20 / 120	23501383
10	1.4408	60.1 mm	-20 / 120	23501377
10	1.4408	60.1 mm	-20 / 120	23501380
10	1.4408	60.1 mm	-20 / 120	23501329
10	1.4408	60.1 mm	-20 / 120	23501385
10	1.4408	60.1 mm	-20 / 120	23501352
10	1.4408	60.1 mm	-20 / 120	23501327
10	1.4408	60.1 mm	-20 / 120	23501378
17	1.4408	60.1 mm	-20 / 120	23501401
17	1.4408	60.1 mm	-20 / 120	23501433
17	1.4408	60.1 mm	-20 / 120	23501430
17	1.4408	60.1 mm	-20 / 120	23501402
17	1.4408	60.1 mm	-20 / 120	23501436
17	1.4408	60.1 mm	-20 / 120	23501439
17	1.4408	60.1 mm	-20 / 120	23501431
17	1.4408	60.1 mm	-20 / 120	23501437
17	1.4408	60.1 mm	-20 / 120	23501434
17	1.4408	60.1 mm	-20 / 120	23501429
17	1.4408	60.1 mm	-20 / 120	23501409
17	1.4408	60.1 mm	-20 / 120	23501438
17	1.4408	60.1 mm	-20 / 120	23501432
17	1.4408	60.1 mm	-20 / 120	23501410
17	1.4408	60.1 mm	-20 / 120	23501435
21	1.4408	60.1 mm	-20 / 120	23501265
21	1.4408	60.1 mm	-20 / 120	23501295
21	1.4408	60.1 mm	-20 / 120	23501298
21	1.4408	60.1 mm	-20 / 120	23501273
21	1.4408	60.1 mm	-20 / 120	23501300
21	1.4408	60.1 mm	-20 / 120	23501292
21	1.4408	60.1 mm	-20 / 120	23501264
21	1.4408	60.1 mm	-20 / 120	23501296
21	1.4408	60.1 mm	-20 / 120	23501291
21	1.4408	60.1 mm	-20 / 120	23501294
21	1.4408	60.1 mm	-20 / 120	23501299
21	1.4408	60.1 mm	-20 / 120	23501293
21	1.4408	60.1 mm	-20 / 120	23501297
21	1.4408	60.1 mm	-20 / 120	23501272

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.