

面

E G

ASCO Solenoid valve 2/2 Type: 32604 series 222 brass internal thread

Characteristics

Series: 222 Type: 32604 Function: Normally closed [NC] Actuation: Indirect-acting Electrical connection: Plug EN 175301-803 type A Housing material: Brass Sealing: EPDM Material coil housing: Epoxy Material shorting ring: Copper Membrane material: PTFE Working time: 100 % Level of protection (IP value): IP65 Emergency manual operation: None Explosion-proof: No Medium temperature: From 0 °C to 165 °C Ambient temperature: From -20 °C to 40 °C

Application

• Steam.Hot water.

Technical Information

• Deactivated when closed.

Size process connection	Process connection	Orifice	Kvs value	Minimum pressure difference	Maximum pressure difference	Coil type	Supply voltage	Power	Starting power	Article
		mm	m³/h	bar	bar					
1/2" (15)	Internal thread (BSPP)	9.5	2.2	0.07	6	400325-101	24V AC	6 W / 15.6 VA	34 VA	11815222
1/2" (15)	Internal thread (BSPP)	9.5	2.2	0.07	6	400325-117	230V AC	6 W / 15.6 VA	34 VA	11395753

PR5697509523842593_EN_19.05.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1



