

WIKA Hydrostatic level transmitter fig. 1241 series IS3 stainless steel




Characteristics

Series: IS-3
Type: 1241
Model: Hydrostatic level transmitter
Measuring method: Pressure
Max. pressure: 1.8 bar
Accuracy class: 0.5 %
Relative linearity deflection: 0.2 % %
Relative repeat accuracy: 0.1 % %
Process connection: External thread [BSPP]
Mounting: Horizontal and vertical
Membrane material: Stainless steel 316Ti
Material switch housing: Stainless steel
Process connection material: Stainless steel 316Ti
Sealing: FPM
Cable material: PUR

Characteristics [2]

With display: No
Output signal: 4 - 20 mA
Electrical connection: Cable
Level of protection [IP value]: IP68
Medium temperature: -20 / 80 °C
Ambient temperature: -15 / 70 °C
Explosion-proof: Yes
Ex-class: II 1/2G Ex ia IIC Ga/Gb T4/T5/T6
ATEX Zone: Zone 0
Approvals: ATEX IECEx, GL



Measuring range	Measuring unit	Type of diaphragm	Size process connection	Supply voltage	Cable length	Article
					m	
0 / 100	mbar	Inner lying	1/2" [15]	10 - 30V DC	5	13472548
0 / 100	mbar	Inner lying	1/2" [15]	10 - 30V DC	2	13472549
0 / 100	mbar	Front lying	1" [25]	10 - 30V DC	5	13472558
0 / 100	mbar	Front lying	1" [25]	10 - 30V DC	2	13472560
0 / 160	mbar	Inner lying	1/2" [15]	10 - 30V DC	2	13472559
0 / 160	mbar	Front lying	1" [25]	10 - 30V DC	2	13472556
0 / 160	mbar	Front lying	1" [25]	10 - 30V DC	5	13472557
0 / 250	mbar	Inner lying	1/2" [15]	10 - 30V DC	5	13472551
0 / 250	mbar	Inner lying	1/2" [15]	10 - 30V DC	2	13472550
0 / 250	mbar	Front lying	1" [25]	10 - 30V DC	2	13472561
0 / 400	mbar	Inner lying	1/2" [15]	10 - 30V DC	2	13472552
0 / 400	mbar	Inner lying	1/2" [15]	10 - 30V DC	5	13472553

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Measuring range	Measuring unit	Type of diaphragm	Size process connection	Supply voltage	Cable length m	Article
0 / 400	mbar	Front lying	1" [25]	10 - 30V DC	2	13472562
0 / 600	mbar	Inner lying	1/2" [15]	10 - 30V DC	5	13472555
0 / 600	mbar	Inner lying	1/2" [15]	10 - 30V DC	2	13472554
0 / 600	mbar	Front lying	1" [25]	10 - 30V DC	2	13472563

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.