

## PARKER Flow meter fig. 8142 & 8182 water

## **Characteristics**

Series: FL **Type:** 8182

Mounting: Vertical Internal spring: No

**Process connection:** External thread (BSPT)

Calibration: Water Accuracy: 2.0 %

Material of connection: Grillon TR55

Housing material: ABS Material float catcher: ABS With needle valve: No Explosion-proof: No

Size process connection	Measuring range	Measuring unit	Material measuring tube	Float material	Max. pressure	Article
					bar	
1/4" [8]	0.06 / 0.55	l/min	Grillon TR55	Stainless steel	10	11814794
3/4" [20]	0.2 / 2	l/min	Grillon TR55	Acetal	10	11814795
3/4" [20]	2 / 10	l/min	Grillon TR55	Stainless steel	10	11814796
3/4" (20)	2 / 22	l/min	Grillon TR55	Stainless steel	10	11814797

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

E-mail: valves@eriks.be

PR69188428344\_EN\_21.05.2024